## scholtès





## BOX WALL HOOD SOHB1930X

Stainless steel and black glass
Width 90 cm
3 speeds + Booster
Max air flow 567 m3/h, Booster 691 m3/h
Max noise level 65 dB, Booster 70 dB
Aluminium grease filters
Carbon filters
Grease and carbon filter saturation indicator
Delayed stop function
2 x 1.5 W LED lighting
Installation for recycling or extraction

Accessory: remote control





ENERGY EFFICIENCY CLASS A

## Scholtes.com

10/2020 The Group reserves the right to modify at any time and without previous notice the products described in this document. It cannot be taken as a contractual document.



## BOX WALL HOOD SOHB1930X

INSTALLATION TYPE	RECYCLING / EXTRACTION
ENERGY EFFICIENCY CLASS	A
TYPE OF CONTROL	ELECTRONIC CONTROL
REMOTE CONTROL	YES
MAX SUCTION, BOOSTER (M3/H)	691
MIN / MAX SUCTION, IN NORMAL OPERATION (M3/H)	219 / 567
NOISE LEVEL IN BOOSTER MODE (DB)	70
NOISE LEVEL AT MAX SPEED IN NORMAL OPERATION (db)	65
NUMBER OF SPEEDS	3
BOOSTER	YES
AUTOMATIC STOP	YES
ANNUAL ENERGY CONSUMPTION (KWH/YEAR)	50
FAN EFFICIENCY CLASS	A
LIGHTING EFFICIENCY CLASS	В
LIGHTING	2 X 1.5 W LED
GREASE FILTERING EFFICIENCY CLASS	В
NUMBER OF CREASE FILTERS	3
CREASE FILTER MATERIAL	ALUMINIUM
CARBON FILTERS INCLUDED	YES
REFERENCE OF CARBON FILTERS	CU003865
GREASE/CARBON FILTER SATURATION INDICATOR	YES/YES
ANTI-RETURN VALVE	YES
INSTALLATION KIT INCLUDED	YES
MOTOR POWER (W)	275
TOTAL POWER (W)	278
VOLTAGE (V), FREQUENCY (HZ), AMPERE (A)	220-240, 50, 10
EXTRACTION DIAMETER (MM)	150
SUPPLIED WITH POWER CORD, IN CM	YES, 200
COLOUR	STAINLESS STEEL AND BLACK GLASS
PRODUCT DIMENSIONS (HXWXD) MM	629.5 X 898 X 500
PACKAGING DIMENSIONS (HXWXD) MM	595 X 1010 X 450
NET WEIGHT (KG)	19.9
GROSS WEIGHT (KG)	26.2
anoss Weiaiti (Na)	20.2

BOX WALL HOOD SOHB1930X

